
TIGER Neo III

JinKO Solar

48QL6-DV

470-490 Watt

MONO-FACIAL MODULE
WITH DUAL GLASS




Higher Power on Front Side

Leading power class based on the enhanced N-type TOPCon platform, achieved through cutting-edge technology and an optimized layout that captures more sunlight.

Optimized Heat resistance

Optimized temperature coefficient achieved via advanced graphical patterning, busbar and multi-cell technology.



25Year Product Warranty | **30**Year Linear Power Warranty | **1**% First-year Degradation | **0.35**% Annual Degradation Over 30 Years

Proven Low Light Performance

Enhanced cell structure ensures superior module performance under low-light conditions.

Industry Leading Warranty

Advanced metallization and iterated module encapsulation deliver superior resistance to PID, LID / LeTID, and UV degradation.

Mechanical Load Enhanced

Certified to withstand:
5400 Pa front side max static test load
2400 Pa rear side max static test load

- IEC61215:2021 / IEC61730:2023
- IEC61701 / IEC62716 / IEC60068 / IEC62804
- ISO9001:2015: Quality Management System
- ISO14001:2015: Environment Management System
- ISO45001:2018: Occupational health and safety management systems

TUV SUD | CE | PV CYCLE | CLEAN ENERGY COUNCIL MEMBER | POSITIVE QUALITY™ Continuous Quality Assurance

JKM470-490N-48QL6-DV-F5-OC

48QL6-DV 470-490 Watt

Mechanical Characteristics

Cell Type	N- type Mono-crystalline
No. of cells	192 (48×4)
Dimensions	1762×1134×30 mm
Weight	21.7 kg
Front Glass	1.6 mm, Anti-reflection Coating
Back Glass	1.6 mm, Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Protection Class	Class II
IEC Fire Type	Class C
Connector Type	PV-JK03M/xy,PV-JK03M2/xy (JinKO) ; PV-KST4-EVO2A/xy,PV-KBT4-EVO2A/xy (Staubli)
Output Cables (Including Connector)	⩾ 4.0 mm² (+): 500 mm , (-): 400 mm or (+): 1400 mm , (-): 1400 mm or Customized Length

* MC4-EVO2 available upon request and subject to availability

Packaging Configuration

Pallet Dimensions	1792×1140×1249 mm
Packing Detail (Two pallets = One stack)	37 pcs/pallets, 74 pcs/stack, 962 pcs/ 40'HQ Container

Specifications (STC)

Maximum Power - Pmax [Wp]	470	475	480	485	490
Maximum Power Voltage - Vmp [V]	30.93	31.11	31.30	31.48	31.66
Maximum Power Current - Imp [A]	15.20	15.27	15.34	15.41	15.48
Open-circuit Voltage - Voc [V]	36.17	36.42	36.67	36.92	37.17
Short-circuit Current - Isc [A]	15.82	15.86	15.90	15.95	16.00
Module Efficiency STC [%]	23.52	23.77	24.02	24.27	24.52
Power Measurement Tolerance	0 ~ + 3 %				
Power Sorting	-5W ~ +15W				
Temperature Coefficient of Pmax	-0.26 %/°C				
Temperature Coefficient of Voc	-0.24 %/°C				
Temperature Coefficient of Isc	0.046 %/°C				


STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5

Application Conditions

Level T_{98} ⩽ 70 °C	- 40 °C to + 70 °C*
Maximum System Voltage	1500 V DC (IEC)
Maximum Series Fuse Rating	30 A


*Short-term up to 85°C; higher operation requires IEC TS 63126 testing


Engineering Drawings



*Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

Electrical Performance





Made in China

© 2026 Jinko Solar Co., Ltd. All rights reserved.

JKM470-490N-48QL6-DV-F5-OC

www.jinkosolar.com

Note: Please read the safety and installation manual before using the product. We reserve the right of final interpretation. The specifications in this datasheet are subject to change without notice.