



Sigen Hybrid Inverter

50.0 / 99.9 / 110.0 / 125.0 kW

- Battery ready, easy upgrades to a PV + ESS system
- Lightweight design, saves transportation and installation costs
- Multiple units in parallel connection, no data logger needed
- Industry-leading AFCI detection, superior safety and reliability
- Instant PV reverse connection alert, ensuring correct installation
- IP66 protection rating, worry-free outdoor usage with easy O&M

Sigen Hybrid Inverter 50.0 / 99.9 / 110.0 / 125.0 kW for Australia

Sigen PV	50M1-HYA-AU	99.9M1-HYA-AU	110M1-HYA-AU	125M1-HYA-AU ¹	Units
DC Input (PV)					
Max. PV input power	100,000	199,800	220,000	220,000	Wp
Max. DC input voltage	1,100				V
Nominal DC input voltage	600 @380/400 Vac, 720 @480 Vac				V
Start-up voltage	180				V
MPPT voltage range	160 ~ 1,000				V
Number of MPP trackers	4	8	8	8	
Number of PV strings per MPPT	2				
Max. input current per MPPT	32				A
Max. short-circuit current per MPPT	50				A
DC Input (Battery)					
Battery module models	SigenStack BAT 12.0				
System configuration quantity range	4 ~ 21				pcs
Max. charge power	50,000	99,900	110,000	121,000 ¹	W
Max. discharge power	50,000	99,900	110,000	125,000 ¹	W
Max. operating current	180				A
AC Output					
Nominal output active power	50,000	99,900	110,000	125,000 ¹	W
Max. output apparent power	50,000	99,900	110,000	125,000 ¹	VA
Max. output active power (cosΦ=1)	50,000	99,900	110,000	125,000 ¹	W
Nominal output current @400Vac	72.5	144.8	159.4	181.2	A
Nominal output current @480Vac	60.2	120.2	132.4	150.4	A
Max. output current @400Vac	72.5	144.8	159.4	181.2	A
Max. output current @480Vac	60.2	120.2	132.4	150.4	A
Nominal output voltage	400/480, 3W+(N)+PE				Vac
Nominal grid frequency	50 / 60				Hz
Power factor	0.8 leading ~ 0.8 lagging				
Total current harmonic distortion	THDi < 3%				
Efficiency					
Max. efficiency @400 Vac	98.6%				
European efficiency @400 Vac	98.3%	98.4%	98.4%	98.3%	
Max. efficiency @480 Vac	98.8%				
European efficiency @480 Vac	98.4%	98.6%	98.6%	98.4%	
Protection					
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter, AC overcurrent/overvoltage/short-circuit protection. Type II DC/AC surge protection, Anti-islanding protection				
General Data					
Dimensions (W / H / D)	918 / 640 / 340				mm
Weight	78				kg
Nighttime power consumption	< 3.5				W
Storage temperature range	-40 ~ 70				°C
Operating temperature range	-30 ~ 60				°C
Relative humidity range	0% ~ 100%				
Max. operating altitude	5,000 (Derating at 4,000m)				m
PV connection type	MC4 (Max. 6 mm ²)				
AC connection type	OT / DT terminal (Max. 240 mm ²)				
Cooling	Smart air cooling				
Ingress protection rating	IP66				
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)				

- Operates at specific temperature. Please contact Sigenenergy for availability.
- The information in this document reflects the current state of technology and is subject to change without notice. For the latest updates, please refer to the Sigenenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.